

## 6 in. (15 cm) Ceiling Speaker

**Item: LPT-A104**

- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:  
Speaker wire  
R12, R14, R22 or R24 Room Modules

| Specifications *       |  |
|------------------------|--|
| Frequency Range        | 60 Hz - 20 kHz, -10 dB, Half Space   |
| Power Capacity         | 30 W Continuous Program Power,<br>80 W Continuous Pink Noise                 |
| Nominal Sensitivity    | 90 dB SPL, 1 W @ 3.3 ft. (1 m)   |
| Nominal Coverage Angle | 110° (Conical Coverage)  |
| Nominal Impedance      | 8 ohms   |
| Termination            | Removable locking connector<br>w/ screw-down terminals, 2 input<br>terminals |
| Woofer                 | 6.5" (165 mm) Polypropylene<br>w/ Rubber                                     |
| Tweeter                | 1/2 in. (13 mm) Mylar Tweeter  |
| Cut out size           | 8.18 in. (208 mm)  |
| Net Weight             | 3.26 lbs. (1.48 kg)  |



\* Specifications are subject to change without notice.

## 6 in. (15 cm) Plenum Rated Ceiling Speaker

**Item: LPT-A104-P**

- Plenum rated to meet fire code.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:  
Speaker wire  
R12, R14, R22 or R24 Room Modules

| Specifications *    |  |
|---------------------|--|
| Frequency Range     | 60 Hz - 20 kHz   |
| Nominal Sensitivity | 89 dB SPL, 1 W @ 3.3 ft. (1 m)   |
| Rated Maximum SPL   | 107 dB, 1 W @ 3.3 ft. (1 m)  |
| Nominal Impedance   | 8 ohms   |
| Power Handling      | 10 - 80 W  |
| Termination         | Removable locking connector<br>w/ screw-down terminals, 2 input<br>terminals |
| Woofer              | 6.5" (165 mm) Polypropylene<br>w/ Rubber                                     |
| Tweeter             | 1/2" (13 mm) Mylar Tweeter   |
| Cut out size        | 9 in. (229 mm)   |
| Net Weight          | 7.53 lbs. (3.42 kg)  |



\* Specifications are subject to change without notice.

## 8 in. (20 cm) Ceiling Speaker

**Item: LPT-A105**

- Larger diameter provides a greater range of sound than the 6 in. ceiling speaker.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:  
Speaker wire  
R12, R14, R22 or R24 Room Modules

| Specifications *       |  |
|------------------------|--|
| Frequency Range        | 50 Hz - 20 kHz, -10 dB, Half Space                                     |
| Power Capacity         | 40 W Continuous Program Power, 100 W Continuous Pink Noise             |
| Nominal Sensitivity    | 91 dB SPL, 1 W @ 3.3 ft. (1 m)   |
| Nominal Coverage Angle | 110° (Conical Coverage)  |
| Nominal Impedance      | 8 ohms   |
| Termination            | Removable locking connector w/ screw-down terminals, 2 input terminals |
| Woofer                 | 8" (203 mm) Polypropylene w/ Rubber                                    |
| Tweeter                | 1/2 in. (12.7 mm) Mylar Tweeter  |
| Cut out size           | 9.88 in. (251 mm)  |
| Net Weight             | 5 lbs. (2.27 kg)   |



\* Specifications are subject to change without notice.

## 4 in. (10 cm) Wall Mount Speaker

**Item: LPT-A106S**

- Use for rooms where speaker cannot be mounted into the ceiling grid structure.
- Excellent sound quality.
- Easily mounted.
- Comes with installation hardware.

Requires:  
Speaker wire  
R12, R14, R22 or R24 Room Modules

| Specifications *       |   |
|------------------------|---|
| Frequency Range        | 85 Hz - 18 kHz                              |
| Nominal Sensitivity    | 88 dB SPL, 1 W @ 1 m                        |
| Power Capacity         | 40 W Continuous Program, 100 W Peak         |
| Nominal Impedance      | 8 ohms                                      |
| Dimensions (W x D x H) | 5.5 x 5.25 x 7.75 in. (14 x 13.3 x 19.7 cm) |
| Net Weight             | 3.78 lbs. (1.72 kg)                         |



\* Specifications are subject to change without notice.