

# SZ 6104

## DCS 6000 Switcher



### Configurations

DCS 6000 Switcher

The SZ 6104 Switcher Box provides the ability to switch DCS LAN Cat-5e cable connections from one source location to another, or to switch from active to inactive, via either auto-power sensing or contact closure, without requiring physical Cat-5e patching. The back panel connections include three (3) sets of RJ45 open/shut pass-through gateways. Also featured on the back panel is one (1) set of three (3) RJ45 connections, that allow switching of the DCS LAN from one (1) source location to another. Finally, there is one (1) D-Sub 9 port for accepting contact closures from an external control system that will trigger the relays. The front panel features eight (8) dip switches, which are manual overrides for the contact closures provided on the D-Sub 9 connector.

### Highlights

- Increases system flexibility and control.
- Cost-effective controlled Cat-5e switching.
- Increases systems redundancy, reliability, and security.
- Allows for room combining, CU redundancy, resource sharing, central control, and security.
- Simple interface to standard control systems.

### Includes

SZ 6104 DCS 6000 LAN Switcher Box

### Used With

CU 6005 DCS 6000 Medium Power Central Control Unit  
EX 6010 DCS 6000 Extension Power Supply  
RP 6004 DCS 6000 Repeater  
AO 6004 DCS 6000 4-Channel Analog Output Module  
JB 6002 DCS 6000 2 Tap-Out Junction Box  
DM 6010 P DCS 6000 Delegate Unit w/Fixed Mic 15.8 in. (40 cm)  
DM 6060 P DCS 6000 Delegate Flush Unit w/Single Channel Selector & Fixed Mic 15.8 (40 cm)

# SZ 6104

## DCS 6000 Switcher

Specifications*		
Interconnections	DCS-LAN Pass-through gateway	Three (3) sets of two (2) RJ45 ports, screened (with auto-termination)
	DCS-LAN Switcher Input	Two (2) RJ45 ports for connection to remote and local Control Units
	DCS-LAN Switcher Output	One (1) RJ45 port for connection to Local System conference units
	D-Sub 9 Port	One (1) D-sub connector - nine (9) pin, for connection to control systems
Power	Power Consumption	max 10W
Physical	Dimensions (H x W x D)	4.65 x 10.39 x 5.04 in. (42 x 264 x 128 mm)
	Color	Black
	Unit Weight	2.6 lbs
	Shipping Weight	4.0 lbs
	Mounting	Free-standing or mounted in a 19" rack

\*Specifications are subject to change without notification.