

DM 6680 P

DCS 6000 Delegate Unit w/5 Voting Buttons for Pluggable Mic

Configurations

DM 6680 P



(GM 6524 shown - sold separately)



The DM 6680 P is a cost effective solution to compliment the same elegant design of the DC 6990 P touchscreen conference unit. Ideal for permanent or temporary meetings with speech, voting and/or language interpretation functions. Together with the DC 6990 P (as a chairman unit), a complete voting system can easily be implemented providing excellent audio quality.

The DM 6680 P has been designed for use in council meetings, board rooms, conference halls, and meeting rooms – everywhere participants need to hear and be heard. The built in channel selector and two headphone jacks make it a cost effective microphone for bilingual applications where voting is required. The portable conference unit includes Speak/Request buttons with a text overlay allowing you to customize functionality.

Highlights

- Yes/No/Abstain and multiple choice options for a complete voting system.
- Elegant, unobtrusive, black units provide a clean aesthetic.
- Button overlays for language and function versatility.
- Lockable XLR socket for added security (GM 65XX series Mic, sold separately).
- Excellent sound quality.
- Cost-effective structured shielded Cat-5e cabling for simple installation (sold separately).

Includes

- DM 6680 P DCS 6000 Delegate Unit w/ 5 Voting Buttons for Pluggable Mic

Used With

- GM 6523 Advanced Pluggable Microphone 15.75 in. (40 cm)
- GM 6524 Advanced Pluggable Microphone 19.7 in. (50 cm)
- DC 6990 P DCS 6000 Single/Dual User Configurable 3.5 in. (9 cm) Touchscreen Unit for Pluggable Mic
- CU 6005 DCS 6000 Medium Power Central Control Unit
- CU 6011 DCS 6000 High Power Central Control Unit
- DM 6010 P DCS 6000 Delegate Unit w/Fixed Mic 15.8 in. (40 cm)
- DM 6060 P DCS 6000 S Delegate Flush Unit w/Single Channel Selector & Fixed Mic 15.8 (40 cm)
- DM 6070 P DCS 6000 S Delegate Unit w/Dual Channel Selectors & Fixed Mic 15.8 (40 cm)

DM 6680 P

DCS 6000 Delegate Unit w/5 Voting Buttons for Pluggable Mic

Specifications*

Audio	Loudspeaker Frequency Response	150 Hz – 15 kHz
	Loudspeaker diameter	3 in. (76 mm)
	Loudspeaker maximum power	3 W RMS
	Channel Selector Frequency Response	100 -14 kHz
	Microphone Connector	3p XLR female
	Headphone Connector	Two (2) 3.5 mm (0.14 in.) stereo headphone connectors
	DCS-LAN	Two (2) RJ45 ports, screened with auto-termination

Controls & Indicators	Microphone Button	Dual button with Red/Green illuminating LED; red indicates microphone is active, green indicates request-to-speak
	Voting Buttons	Five (5) buttons for voting

Power	Power Consumption	2 Watts
-------	-------------------	---------

Physical	Dimensions (H x W x D)	2.95 x 10.47 x 6.10 in. (75 x 266 x 155 mm)
	Color	Black
	Unit Weight	2.0 lbs. (0.9 kg)
	Shipping Weight	3.0 lbs. (1.4 kg)
	Mounting	Tabletop (portable or fixed)

*Specifications are subject to change without notification.