

JB 6002/6004

DCS 6000 Tap-Out Junction Box



JB 6002

JB 6004

Configuration

JB 6002 - DCS 6000 2 Tap-Out Junction Box
JB 6004 - DCS 6000 4 Tap-Out Junction Box

The Tap-Out Junction Box provides two (2) or four (4) tap-outs from the daisy-chain. Each tap-out port in the junction box is isolated from the rest of the system, thus improving system redundancy and reliability. The maximum cable length from each junction box port is 32.8 ft. (10 m). Each tap-out port can handle one (1) delegate mic, one (1) interpreter set or four (4) channel selectors.

Highlights

- Cost-effective structured Cat-5e cabling.
- Increases systems redundancy and reliability.
- Flexible cabling topology.

Includes

JB 600x

Used With

CU 6005	DC 6990 P
CU 6011	AM 6040
EX 6010	DM 6060 F
AO 6008	CM 6060 F
PS 6000	DM 6510 F
RP 6004	DM 6560 F
AO 6004	CM 6660 F
JB 6002	MU 6040 D
JB 6004	MU 6040 C
DM 6010 P	MU 6042 D
DM 6060 P	DV 6501 F
DM 6070 P	CS 6032 FHB1
CM 6070 P	IS 6132 P
DM 6090 P	CO RJ45 F
CM 6090 P	CO RJ45 M-5.2

Requires

Requires a cable	
EC 6000-05	EC 6000-05
EC 6000-0.5	EC 6000-10
EC 6000-01	EC 6000-20
EC 6000-02	EC 6000-30
EC 6000-03	EC 6000-50

Specifications

Audio	DCS-LAN	Two (2) RJ45 ports, screened with auto-termination
	DCS-LAN Tap-outs	Two (2) Four (4) isolated ports for connection of one conference unit each.

Power	Power Consumption	0.5 W
-------	-------------------	-------

Physical	Dimensions (H x W x D) JB 6002	0.94 x 3.19 x 4.13 in. (24 x 81 x 105 mm)
	Dimensions (H x W x D) JB 6004	1.85 x 3.78 x 4.25 in. (47 x 96 x 108 mm)
	Color	black
	Unit Weight JB 6002	7.05 oz. (200 g)
	Unit Weight JB 6004	14.11 (400 g)
	Shipping Weight	1.0 lbs. (454 g)
	Mounting	Free-standing or mounted in a 19" rack.