MB 2932
DCS 6000 Interpreter Booth for 2 Interpreters

Don't miss a single sound.

www.listentech.com

Configuration

MB 2932

The MB 2932 Interpreter booth is intended for portable use or fixed installations and allow for two (2) interpreters. The booth consists of four (4) window-panels, three (3) blind-panels, a door-panel, a table and two (2) roof-panels and can easily be extended. Two (2) ventilation fans are included and it exceeds ISO 4043 sound insulation standards.

Set-up time is approx. 5-10 minutes. Each booth must be delivered with a flight case or transport packaging (sold separately).

Includes

MB 2932

Requires

Requires transport materials.

MB 2932 EP

MB 2932 FC

Highlights

- Excellent sound insulation.
- 5-10 minutes to set-up.
- Sizeable.

Used With

IS 6132 P
MB 2932 EP
MB 2932 FC

Specifications		
Audio	Sound Insulation	According to ISO 4043
Interconnection	Fans	Two (2) main cords to power the fans
Physical	Outside dimensions (H x W x D)	6.6 x 5.3 x 5.3 ft. (2.0 x 1.6 x 1.6 m)
	Outside Color	Grey 871 (RAL 7042)
	Inside Color	White / Dark Grey
	Unit Weight	463 lbs. (210 kg)
	Shipping Weight	Varies based on packaging type

Listen Technologies Corporation • 14912 Heritagecrest Way • Bluffdale • Utah 84065-4818 U.S.A.
+1.801.233.8992 • +1.800.330.0891 North America • +1.801.233.8995 Fax

Listen Technologies Corporation All rights reserved 122007