

MU 6040

DCS 6000 Single Delegate/Chairman

Microphone Unit for Flush Panels



Configuration

- MU 6040 D - DCS 6000 Single Delegate Microphone Unit for Flush Panels
- MU 6040 C - DCS 6000 Chairman Microphone Unit for Flush Panels

The MU 6040 Single Microphone Unit is required to connect flush panels or 3rd party dynamic microphones and/or loudspeakers to the DCS 6000 system. Delegate positions require a MU 6040 D and chairman positions require a MU 6040 C. The compact and robust unit is typically mounted under the table or inside a floor box. The DCS-LAN daisy chain loops from one MU 6040 to the next with shielded FTP or STP Cat-e5 cables (sold separately).

Highlights

- Cost-effective structured Cat-5e cabling.
- Robust and compact.
- Can be used to integrate 3rd party dynamic and condenser microphones and loudspeakers.

Requires

Requires a flush panel or handheld mic.

FD 4010 FHB-4432-GB-100
FC 4010 FHB-4432-GB-100
FD 4011 FHB-4432-GB-100
FC 4011 FHB-4432-GB-100

HM 4042

Requires a cable.

EC 6000-0.5
EC 6000-01
EC 6000-02
EC 6000-03
EC 6000-05
EC 6000-10
EC 6000-20
EC 6000-30
EC 6000-50

Used With

CU 6005	DM 6090 P
CU 6011	CM 6090 P
EX 6010	DC 6990 P
AO 6008	AM 6040
PS 6000	DM 6060 F
RP 6004	CM 6060 F
AO 6004	DM 6510 F
JB 6002	DM 6560 F
JB 6004	CM 6660 F
FD 4010 FHB-4432-GB-100	MU 6040 D
FC 4010 FHB-4432-GB-100	MU 6040 C
FD 4011 FHB-4432-GB-100	MU 6042 D
FC 4011 FHB-4432-GB-100	DV 6501 F
HM 4042	CS 6032 FHB1
DM 6010 P	IS 6132 P
DM 6060 P	CO RJ45 M-5.2
DM 6070 P	CO RJ45 F
CM 6070 P	

Includes

MU 6040 x

Specifications

Audio	System Frequency Response	100 Hz - 15 kHz
Interconnections	Microphone, lsp, control connection	Female D-sub HD15 connector (VGA monitor connector) to connect the flush panel
	DCS-LAN	Two (2) RJ45 ports, screened with auto-termination
Power	Power Consumption	2.5 W
Physical	Dimensions (H x W x D)	1.02 x 4.53 x 4.80 in. (26 x 115 x 122 mm)
	Color	black
	Unit Weight	0.88 lbs. (0.40 kg)
	Shipping Weight	1.0 lbs. (0.45 kg)
	Mounting	Under table or in floor box